

## MAGPRO 75/4s

The robust allrounder with 4 speeds:  
twist drilling, core drilling & tapping



### Specifications

Power input	1.800 W
Voltage	230V/50HZ or 115V/60Hz
Speed (no load / full load)	1: 210 / 120 rpm 2: 270 / 160 rpm 3: 410 / 290 rpm 4: 530 / 310 rpm
Shank	Weldon 19/32 mm, MT3
Max. Ø core drills x L	12 - 75 x 75 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT3	32 x 150 mm
Max. depth x Ø	75 x 75 mm
Stroke	100 mm
Magnetic adhesion	32.000 N
Magnetic surface	200 x 100 mm
Cooling system	integrated, automatic
Net weight	24,8 kg

Description	Ref.
<b>MAGPRO 75/4s</b> - 230V in suitcase with safety chain, maintenance tools and MT3/19 mm adapter	490160
<b>MAGPRO 75/4s</b> - as above with 115V	490161
<b>MT3 Quick change adapter</b> for thread cutter shank M3-M14	490162
<b>Quick change inserts</b> M3-M14 (single)	490162 M3-14
<b>MT3 Quick change adapter</b> for thread cutter shank M5-M22	490165
<b>Quick change inserts</b> M5-M22 (single)	490162 M5-22
<b>Weldon 32/MT3 shank</b> for core drills from Ø 61 mm	490163
<b>Core drill set</b> 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
<b>Drill chuck</b> 16 mm and adapter	490164
<b>Pipefix clamping system</b> for pipes Ø 32 - 600 mm	490010BIG
<b>High Performance Cutting Oil Spray</b> (400 ml)	490020