



Management System ISO 9001:2015

www.tuv.com ID 9105068261

MAGPRO 35 - Power pack

Core drilling in all positions!

Twist drilling up to **Ø 13 mm** Core drilling from **Ø 12 - 35 mm** Shank Weldon 19 mm

Optional:

- Core drill with pilot pin
- 13 mm core drill and adapter
- Quick release
- Magnetic chip collector
- High Performance Cutting Oil Spray

Specifications

Power input	1.100 W
Voltage	230V/50HZ or 115V/60Hz
Core & Twist drilling	620 / 350 rpm (no load / full load)
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 35 x 50 mm
Max. Ø twist drills x L	13 x 110 mm
Stroke	80 mm
Magnetic adhesion	15.000 N
Magnetic surface	165 x 80 mm
Cooling system	integrated, automatic
Net weight	12 kg





Description	Ref.
MAGPRO 35 - 230V delivery in suitcase with safety chain and maintenance tools	490150
MAGPRO 35 - as above with 115V	490110
Accessories (optional)	Ref.
Core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Drill chuck and adapter 13 mm	490152A
Quick release for MAGPRO 35	490151
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020

PERFORMANCE RELIABILITY COST-EFFECTIVENESS