



Management System ISO 9001:2015

www.tuv.com ID 9105068261

# **MAGPRO 35 Semi Automatic**

### Core drilling with automatic feed

- Automatic drilling for core drills from • Ø 14 to 30 mm
- Hand operation from Ø 12 to 35 mm •
- Automatic feed activation with crank handle •

#### **Optional:**

- **Ouick** release
- 13 mm chuck with adapter
- Magnetic chip collector •
- High Performance Cutting Oil Spray •

## **Specifications**

Power input	1.100 W
Voltage	230V/50HZ
Speeds	620 / 350 rpm (no load / full load)
Shank	Weldon 19 mm
Max. Ø core drills x L	12 - 35 x 50 mm
Max. Ø twist drills x L	13 x 110 mm
Max. depth x Ø	50 x 35 mm (Hand feed) 45 x 30 mm (Auto feed)
Stroke	70 mm
Magnetic adhesion	15.000 N
Magnetic surface	165 x 80 mm
Cooling system	integrated, automatic
Net weight	17 kg



Description	Ref.
MAGPRO 35 - 230V delivery in suitcase with safety chain and maintenance tools	490180
Accessories (optional)	Ref.
<b>Core drill set 30 mm</b> Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Drill chuck and adapter 13 mm	490152A
Quick release for MAGPRO 35	490151
Magnetic chip collector	490153
High Performance Cutting Oil Spray for optimal cooling and higher cutting performance (400 ml)	490020



#### PERFORMANCE RELIABILITY **COST-EFFECTIVENESS**