

Super Hand Dry Cutter 8320 Air - air operated incl. Ø 320/ 84T saw blade

DRY-CUT TECHNOLOGY Dry cutting without lubricant

- Ideal for cutting **sandwich panels**, trapezoidal sheet, trunking and cable ducting, steel pipes and nonferrous metals, composite materials etc.
up to cutting depth of 120 mm on guide rail
- Guard closed, prevents flying chips to the user
- Integrated chip collector, connector for optional extraction device
- LED overload indicator:
green: ok | orange: warning | red: over load
- Lightweight magnesium: **11 kg**

Optional accessory:

- **Cutting guide rail 1.400 mm** with quick fixation
- Ideal for clean and straight cutting of sandwich panels

Specifications

	Operating pressure (flow pressure)	6 bar
	Motor output	1.800 W
	No load speed	1.200 min ⁻¹
	Air consumption	ca 2 m ³ /min
	Air connection	R½" Female
	ID of hose	> Ø 16 mm
	Net weight	11 kg
	Blade size	320 mm
	Noise level (1 m distance)	95 dB(A)
	Vibration level no load speed	< 2,5 m/s ²



 Description	Ref.
Super Hand Dry Cutter 8320 -Air delivered with Ø 320/84T saw blade	608200

 Saw blades	Ref.
HM saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T	608276
HM saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 72T	608278
HM saw blade Ø 320 x 2,2 x 1,8 x 25,4 x 84T NSF - for stainless steel, food & construction	608276NSF

 Accessories (optional)	Ref.
Cutting guide rail 1.400 mm	608275D
Cutting guide rail 1.400 mm + 2 C-clamps	608275SET
Connector for cutting guide rail	608275B
C-Clamp for cutting guide rail (single)	608275C



saw blade 608276 included



heavy duty case included