



JEPSON Wraparound Tube Sander/ Polisher 760/40

- Applicable for rough grinding up to mirror polishing
- High efficiency motor with variable fullwave feedback
- Electronic speed control with soft start
- High stable pulleys allow precise control of abrasive belts
- Tool-free change of abrasives
- The large wraparound angle allows easy and fast preparing and finishing of tube constructions (e.g. Railings)

Specifications

PERFORMANCE RELIABILITY

COST-EFFECTIVENESS

Power input	1.200 W
Voltage	230V/50Hz
No load speed	1.600 ~ 3.200 rpm
Surface speed	3 ~ 12 m/s
Max. belt length	760 mm
Max. belt width	40 mm
Net weight	3,4 kg



Accessories included

Description	Ref.
<i>JEPSON</i> Wraparond 760/40 - Delivery in hard shell case with accessories	495050

- 1. Hard shell case 572 x 362 x 238 mm
- **2.** Sandpaper belts:
 - 80 (40 x 760 mm) one piece each
 - 100 (40 x 760 mm) one piece each
 - 120 (40 x 760 mm) one piece each

3. Surface conditioning belt 40 x 760 mm

For optional accessories see page 2



Tel.: +49 (0)2403 64 55 0 | info@jepson.de | www.drycutter.com





Accessories for JEPSON Wraparound Tube Sander 760/40

High Performance Zircon Abrasive Belts

Description:

Cotton/polyester backing with additive, aluminium oxide grain, double resin, close coat.

Main features and benefits:

Extremely long life and highly efficient removal. Coarser grits are suitable for heavy scrubbing of steel and cast iron. It is also suitable for wet applications.

Recommended applications:

Grinding and cleaning, deburring, removing small protruding welded surfaces or welding spots.

Work surfaces:

Standard steel, stainless steel, non ferrous metals, cast iron, alloys.



Description as above	Packaging	Reference
Abrasive belts 40 x 760mm - P080	10 pieces	495WS080
Abrasive belts 40 x 760mm - P100	10 pieces	495WS100
Abrasive belts 40 x 760mm - P120	10 pieces	495WS120

Surface Conditioning Belts X-Flex

This material is unique in the market. Its particular structure makes it very flexible and it prevents delamination. Ideal to work in narrow belts form and it is easy to fit on very compact machinery.

Description as above	Packaging	Reference
X-Flex - Brown 40 x 760 mm - coarse	20 pieces	495WS103
X-Flex - Red 40 x 760 mm - medium	20 pieces	495WS104
X-Flex - Blue 40 x 760 mm - very fine	20 pieces	495WS105

